

Item Number:

4745

High-Vis Vest Full Body Harness With Back & Side D-Rings

Features:

- Dorsal D-rings for fall arrest
- Side D-rings for work positioning
- Tongue buckle leg straps and mating buckle chest closure
- ANSI compliant DOT Class 2 reflective vest
- 1 lanyard keeper
- Sizes Available: Universal Harness with L/XL Vest and 2XL Harness with 2X/3X Vest
- Vest Color: Lime

Material Specifications

Webbing:	Polyester; Min. 5,000 lbs. tensile strength
D-Rings:	Alloy Steel; Min. 5,000 lbs. tensile strength
Buckles/Adjusters:	Alloy Steel; Min. 3,375 lbs. tensile strength

Performance Specifications

Tensile Strength:	Min. 5,000 lbs.
Max. Capacity:	425 lbs. To maintain ANSI Z359 compliance, limit total user weight to 310 lbs.

Relevant Standards

OSHA:	CFR 1926.502, CFR 1910.66
ANSI:	Z359

Warnings:

- Read, understand, and follow all labels and instructions prior to use
- Inspect before each use
- Remove from service if there is evidence of damage or excessive wear
- Never attach a Shock Absorbing Lanyard to the Front or Side D-rings



Warning: this specification sheet provides an overview of products available from Northern Safety/FallTech. Care has been taken to assure the accuracy of the information. It does not provide important product warnings and instructions. Northern Safety/FallTech recommends all users of fall protection equipment undergo thorough training, and that all warnings and instructions provided with these products be thoroughly read and understood prior to use. Failure to read and follow all product warnings and instructions could result in serious injury or death.